HSB35H6PF25, Heavy Wall Cross-Linked Polyolefin Heat Shrink Tubing, #10-14 AWG, 1000 V, 6.00" L, Flame Retardant.



By Burndy
Catalog # HSB35H6PF25

Heavy Wall Cross-Linked Polyolefin Heat Shrink Tubing, #10-14 AWG, 1000 V, 6.00" L, Flame Retardant.

Application

For Direct Burial

General

Catalog Number	HSB35H6PF25
Connector Type	HEAVY WALL TUBES
EU RoHS Indicator	Yes
Material	Cross-linked Polyolefin
Sub Brand	HEAT SHRINK
Type	HS-H-PF, Heavy Wall, Flame Retardant
UPC	781810214794

Conductor Related

Conductor Range	#14 AWG to #10 AWG
Conductor Size	14AWG - 10AWG

Certifications And Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Carton Quantity	625
Minimum Pack Quantity	1

Product Assets

Catalogs - BURNDY Master Catalog - Section D - Shrink Tubing
Catalogs - Full Line BURNDY Catalog
Catalogs - Section D - Shrink Tubing
Literature - Polyolefin Thin Wall Heat Shrink Cross Reference Guide
Product Cross Section Image(s) - BUR_HSB35H6PF25_LineArt
Sales Drawings - SD211942-01
Video - Heat Shrink Product Overview & Installation

©2024 Hubbell Incorporated. All rights reserved.