YSD28R28R, Aluminum Sleeve with Solid Center Barrier



By Burndy
Catalog # YSD28R28R

AL compression sleeve with solid center barrier, Designed for commercial and heavy residential services, Color Code: Pink (Side A), Pink (Side B)

Features

- Aluminum compression sleeve with solid center barrier
- Designed for commercial and heavy residential services, the sleeve is installed with standard tooling
- Pre-filled with PENETROX Joint Compound and Capped

Application

For Combinations Of Copper, Aluminum, ACSR, 6201, 5005 and Compressed Conductors

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	BABA Compliant (All status valid till December 2025)
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No

Conductor

Conductor - ACSR Str Size A	4/0 (6/1) Penquin AWG
Conductor - ACSR Str Size B	4/0 (6/1) Penquin AWG
Conductor - AL Str Size A	4/0 AWG
Conductor - AL Str Size B	4/0 AWG
Conductor - Copper Str Size A	4/0 AWG
Conductor - Copper Str Size B	4/0 AWG

Dimensions

Dimension - Outside Diameter inch	.3125 in
Dimension - L Length Overall mm	102 mm
Dimension - Length Overall inch	4 in

General

Die Index	249;K-840
Trade Name	LINKIT™
Prefilled Oxide Inhibitor	Y
Sub Brand	LINKIT
Plated	N
Type	Service Entrance, Uninsulated
UPC 12 Digit	781810146408
UPC 14 Digit GTIN	00781810146408
Material	Aluminum
Plating Type	Unplated
UPC	781810146408
Color Code - Side A	Pink
Color Code - Side B	Pink

Logistics

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	7400

Product Assets

Catalog [English]

© 2025 Hubbell Incorporated. All rights reserved