BURNDY

YSV1014G2, Uninsulated Reducing Splice For 12 - 10 AWG and 20 - 14 AWG



By Burndy
Catalog # YSV1014G2

Uninsulated Reducing Splice For 12 - 10 AWG and 20 - 14 AWG

Features

- Manufactured from seamless tubing
- High quality design with no seams to split
- Electrolytic copper provides maximum conductivity, low resistance and ductility for excellent crimp forming properties
- Electro-tin plating provides durable long lasting resistance to corrosion
- Positive center wire stops for proper dept of wire insertion
- Marked with wire size providing easy wire size identification
- HYLINK splice connectors feature inspection holes providing easy visual inspection of proper wire insertion

Application

For Splicing Two Different Size Wires

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No

Conductor

Conductor - Copper Str Size	• 20 • 18 • 16 • 14 • 12 • 10
Conductor - Copper Flex I Size B	• 20 • 18 • 16 • 14
Conductor - Copper Flex I Size B Range	20-14
Conductor - Copper Flex K Size A	10
Conductor - Copper Flex K Size A Range	10
Conductor - Copper Flex K Size B	• 20 • 18 • 16 • 14
Conductor - Copper Flex K Size B Range	20-14
Conductor - Copper Flex M Size A	10
Conductor - Copper Flex M Size A Range	10
Conductor - Copper Flex M Size B	• 20 • 18 • 16 • 14
Conductor - Copper Flex M Size B Range	20-14
Conductor - Copper Flex G Size A	10
Conductor - Copper Flex G Size A Range	10
Conductor - Copper Flex G Size B	• 20 • 18 • 16 • 14
Conductor - Copper Flex G Size B Range	20-14
Conductor - Copper Flex H Size A	10
Conductor Size	20 - 14 AWG
Conductor - Copper Flex H Size A Range	10
Conductor - Copper Flex H Size B	• 20 • 18 • 16 • 14
Conductor - Copper Str Size Range	20 AWG - 10 AWG
Conductor - Copper Flex H Size B Range	20-14
Conductor Type	• CU C Str-Size • CU C Solid-Size • CU C Str Aircraft-Size
Conductor - Copper Flex I Size A	10
Conductor - Copper Flex I Size A Range	10

Configuration

Connector Type	Reducer

Current

Voltage - Maximum	35000 V

Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Dimension - L Length Overall mm	20 mm
Package Height	0.000 in
Dimension - A Outside Diameter inch	0.21 in
Dimension - B Length fraction	5/16 in
Dimension - B Outside Diameter inch	0.16 in
Dimension - B Length inch	0.31 in
Dimension - Length BB inch	0.27 in
Dimension - Length Overall inch	0.77 in

General

Trade Name	HYREDUCER™
Sub Brand	HYREDUCER
Plated	Y
Feature - Barrel Style	Chamfered
Type	Splice
UPC 12 Digit	781810026403
UPC 14 Digit GTIN	00781810026403
Material	Copper
Plating Type	Tin
UPC	781810026403

Logistics

Minimum Pack Quantity	500
Carton Quantity	500

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved