BIBD3503, Double Sided Three Conductor Clear Insulated Mult-Tap Connector

By Burndy
Catalog # BIBD3503



Aluminum Multiple Tap Connector, Clear Insulated, 3 Port, 2 Sided Entry, 10 AWG-350 kcmil, Al/Cu Rated

Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

Application

For Indoor Use Only, Copper Or Stranded Aluminum

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Buy America(n) Qualified	BABA Compliant (All status valid till December 2025)
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - Copper Str Size	10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;300 kcmil;350 kcmil
Conductor - AL Str Size	8 AWG;6 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;266 kcmil;300 kcmil;336 kcmil;350 kcmil
Conductor - AL Str Size Range	8 AWG-350 kcmil
Conductor Size	10 AWG-350 KCMIL
Conductor - Copper Str Size Range	10 AWG - 350 kcmil
Conductor Type	AL C Str-Size;CU C Str-Size

Configuration

Physical Attribute - Number of Screws	3
Connector Type	Multi Tap
Number Of Ports	3

Current

Voltage - Maximum	600 V

Dimensions

Dimension - L Length Overall mm	80 mm
Dimension - Height fraction	2.5 in
Dimension - Height inch	2.50 in
Dimension - Height mm	63.5 mm
Dimension - Width inch	3.00 in
Dimension - Width mm	76 mm
Dimension - Length Overall inch	3.13 in

General

Material - Hardware	Aluminum
Insulation Type	Plastisol
Trade Name	UNITAP™
Insulation	Y
Sub Brand	UNITAP
Physical Attribute - Screw Type	Allen
Plated	N
Type	BIBD, Multi-Port
UPC 12 Digit	781810133446
UPC 14 Digit GTIN	00781810133446
Material	Aluminum
Hex Key	5/16
Plating Type	Unplated
UPC	781810133446

Logistics

Minimum Pack Quantity	1
Carton Quantity	24
Pallet Quantity	1344

Operational

Temperature Rating	194

Product Assets

Catalog [English]

Catalog [English]

© 2025 Hubbell Incorporated. All rights reserved