UGSKIT2, Watertight Underground Splice Kit, Dual Rated



By Burndy
Catalog # UGSKIT2

8-2 AWG Dual Rated Mechanical Splice with 2 Heavy Wall Heat Shrink Sleeves, Al/Cu Rated

Features

- Type UGSKIT are underground splice kits (watertight) for aluminum or copper
- Kit consists of a standard splice/reducer and includes heavy wall heat-shrink sleeve
- Dual rated for use with aluminum and copper
- Connector is installed with common installation tools
- Both heavy wall heat shrink sleeves are lined with adhesive material providing a watertight splice

Application

For All Aluminum or Copper/Aluminum Combinations, UF Direct Burial

Specifications

Certification - UL Recognized	No
Buy American Compliant	No
Certification - cULus	No
Industry Standard(s)	UL486D
Certification - ETL	No
Standards - Industry Standards Met	UL486D
Standards - RoHS Compliance Status	CM
Certification - UL Listed Direct Burial	Yes
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - AL Str Size	• 8 AWG • 6 AWG • 4 AWG • 3 AWG • 2 AWG
Conductor - AL Str Size Range	8 AWG-2 AWG
Conductor - Copper Str Size	• 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG
Conductor Size	8-2 AWG
Conductor - Copper Str Size Range	8 AWG-2 AWG

Configuration

Connector Type	Splice/Heat Shrink Kit

Current

Rating - Minimum Voltage	600

Dimensions

Package Height	0.000 in
Dimension - Height mm	0 mm
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	35 mm
Dimension - Length Overall inch	1.38 in
Hex Size	Slot

General

Product Family	MECHANICAL
Physical Attribute - Screw Type	Allen
Plated	No
Sub Brand	SPLICE KIT
Product Type	Splice Reducer
UPC	781810175279
Type	UGSKIT, Watertight/ Underground
Material	Aluminum
Plating Type	Unplated
UPC 14 Digit GTIN	00781810175279

Logistics

Minimum Pack Quantity	1
Pallet Quantity	1050
Carton Quantity	10

Operational

Temperature Rating	194

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved