BURNDY

BIBS45, Single Sided Five Conductor Clear Insulated Multi-Tap Connector



By Burndy
Catalog # BIBS45

Aluminum Multiple Tap Connector, Clear Insulated, 5 Port, 1 Sided Entry, 14-4 AWG, Al/Cu Rated

Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

Application

For Indoor Use Only, Copper Or Stranded Aluminum

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - AL Str Size Range	14 AWG - 4 AWG
Conductor Size	14-4 AWG
Conductor - Copper Str Size Range	14 AWG - 4 AWG
Conductor Type	AL C Str-Size;CU C Str-Size

Configuration

Physical Attribute - Number of Screws	5
Connector Type	Multi Tap
Number Of Ports	5

Current

Voltage - Maximum	600 V
Operating Voltage	600 V

Dimensions

Dimension - L Length Overall mm	61 mm
Dimension - Height inch	1.25 in
Dimension - Height mm	31.8 mm
Dimension - Screw Size inch	1/4
Dimension - Width inch	1.25 in
Dimension - Width mm	32 mm
Dimension - Length Overall inch	2.39 in

General

Insulation Type	Plastisol
Trade Name	UNITAP™
Insulation	Y
Sub Brand	UNITAP
Physical Attribute - Screw Type	Allen
Plated	N
Type	BIBS, Multi-Port
UPC 12 Digit	781810223833
UPC 14 Digit GTIN	00781810223833
Material	Aluminum
Hex Key	1/8
Plating Type	Unplated
UPC	781810223833

Logistics

Minimum Pack Quantity	1
Carton Quantity	99
Pallet Quantity	6336

Operational

Temperature Rating	194

Product Assets

Catalog [English]
Catalog [English]

© 2025 Hubbell Incorporated. All rights reserved