BURNDY

BITO600, Opposite Side Two Conductor Clear Insulated Multi-Tap Connector



By Burndy
Catalog # BITO600

Aluminum Multiple Tap Connector, Clear Insulated, 2 Port, 2 Sided Entry, 4 AWG-600 kcmil, Al/Cu Rated

Features

- Type BIT and BITO (Offset) Multi-tap connectors are installed quickly and easily
- Suitable for use on Code conductor
- UL486B Listed, Dual-rated AL9CU.

Application

For Indoor Use Only, Copper Or Stranded Aluminum

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - AL Str Size Range	4 AWG - 600 kcmil
Conductor Size	4 AWG-600 KCMIL
Conductor - Copper Str Size Range	4 AWG - 600 kcmil
Conductor Type	AL C Str-Size;CU C Str-Size

Configuration

Physical Attribute - Number of Screws	2
Connector Type	Multi Tap
Number Of Ports	2

Current

Voltage - Maximum	600 V
Operating Voltage	600 V

Dimensions

Dimension - L Length Overall mm	69 mm
Dimension - Height inch	2.75 in
Dimension - Height mm	70.00 mm
Dimension - Width inch	3.00 in
Dimension - Width mm	76 mm
Dimension - Length Overall inch	2.72 in

General

Material - Hardware	Aluminum
Insulation Type	Plastisol
Trade Name	UNITAP™
Insulation	Y
Sub Brand	UNITAP
Physical Attribute - Screw Type	Allen
Plated	N
Type	BIT
UPC 12 Digit	781810225264
UPC 14 Digit GTIN	00781810225264
Material	Aluminum
Hex Key	3/8 in
Plating Type	Unplated
UPC	781810225264

Logistics

Minimum Pack Quantity	1
Carton Quantity	50
Pallet Quantity	1800

Operational

Temperature Rating	90°C

Product Assets

Catalog [English]
Catalog [English]

© 2025 Hubbell Incorporated. All rights reserved