HYTOOL™ Series, Hand-Operated Crimper, Installs #14 - 4/0 AWG, Permanent O and D3 grooves



By Burndy
Catalog # MD68

HYTOOL™ #14-4/0, Permanent O/D3

Features

- Ergonomically designed, one-piece, composite polymer handles
- Comfort grip handles
- Time-proven steel jaw designs
- No tool adjustment required
- 99,000 crimp/cycle life
- Positive lock, spring loaded die retainer buttons
- PTFE impregnated steel/bronze bushings and stainless steel pins
- Electroless nickel plated jaws and jaw links

Application

Crimping

Specifications

Buy American Compliant	No
EU RoHS Indicator	Yes
Standards - RoHS Compliance Status	EX

Conductor

Crimping Ranges	• Copper: 10 sol. - 500 Kcmil • Copper Flex: #8 to 350 kcmil

Dimensions

Length	25.38 in
Width	7.04 in
Weight	6 lb.
Height	2 in
Dimensions	25.38 in x 7.04 in x 2 in

Force Related

Crimp Force Capacity	4.5 ton

General

Sub Brand	HYTOOL
Series	HYTOOL™ Series
Trade Name	HYTOOL™
Application - For Use On	Copper, Aluminum, ACSR, Steel, Copperweld, Alumoweld, 6201, 5005, Compressed and Compact Conductors
UPC 12 Digit	781810446553
UPC 14 Digit GTIN	00781810446553
Tool Type	Hand Operated Crimper
UPC	781810446553
Die Type	W Die and X Die

Logistics

Package Contents	Tool only
Minimum Pack Quantity	1

Product Assets

Catalog [English]

© 2025 Hubbell Incorporated. All rights reserved