HSC200FR, PVC Clear Heat Shrink Tubing, 800-1000 Code, 500-750 Flex, 600 V, Fire Retardant.



By Burndy
Catalog # HSC200FR

Heat shrink tubing, Conductor range: 800-1000 (Code), 500-750 (Flex)

Features

- Flame Retardant
- Flexible Polyvinylchloride
- 2:1 Shrink Ratio
- 600 Volts

Application

For Terminations And Splices

Specifications

Buy American Compliant	No
EU RoHS Indicator	Yes
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	No

Conductor

Conductor Size	800kcmil - 1000kcmil

Configuration

Connector Type	CLEAR TUBES

Dimensions

Length	300 in
Width	2 in
Height	2 in
Dimensions	300 in x 2 in x 2 in

General

Sub Brand	VISISHRINK
Trade Name	VISI-SHRINK™
Color	Clear
Type	HSC-FR, Thin Wall, Flexible, Fire Retardant
Material	Polyvinyl chloride
UPC	781810266236

Logistics

Minimum Pack Quantity	1
Carton Quantity	8
Pallet Quantity	48

Product Assets

Catalog [English]

© 2025 Hubbell Incorporated. All rights reserved