HSC34FR, Vinyl Fire Retardant Clear Heat Shrink Tubing, 1/0-3/0(Code) #2-1/0(Flex), 600V.



By Burndy
Catalog # HSC34FR

Heat shrink tubing, Conductor range: 1/0-3/0 (Code), #2-1/0 (Flex)

Features

- Flame Retardant
- Flexible Polyvinylchloride
- 2:1 Shrink Ratio
- 600 Volts

Application

For Terminations And Splices

Specifications

Buy American Compliant	No
EU RoHS Indicator	Yes
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	No

Conductor

Conductor Size	1/0AWG - 3/0AWG
Conductor Range	#2 AWG to # 1/0 AWG

Configuration

Connector Type	CLEAR TUBES

Dimensions

Length	600 in
Width	0.75 in
Height	0.75 in
Dimensions	600 in x 0.75 in x 0.75 in

General

Sub Brand	VISISHRINK
Trade Name	VISI-SHRINK™
Color	Clear
Type	HSC-FR, Thin Wall, Flexible, Fire Retardant
Material	Polyvinyl chloride
UPC	781810266250

Logistics

Minimum Pack Quantity	1
Carton Quantity	16
Pallet Quantity	128

Product Assets

Catalog [English]

© 2025 Hubbell Incorporated. All rights reserved