YSV10, Uninsulated Splice For 12 - 10 AWG



By Burndy
Catalog # YSV10

Uninsulated Splice For 12 - 10 AWG

Features

- Manufactured from seamless tubing
- High quality design with no seams to split
- Electrolytic copper provides maximum conductivity, low resistance and ductility for excellent crimp forming properties
- Electro-tin plating provides durable long lasting resistance to corrosion
- Positive center wire stops for proper dept of wire insertion
- Marked with wire size providing easy wire size identification
- HYLINK splice connectors feature inspection holes providing easy visual inspection of proper wire insertion

Application

For All Heavy Duty Industrial And General Purpose Applications

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - Industry Standards Met	UL486
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Copper Str Size	• 12 • 10
Conductor - Copper Solid Size	• 12 • 11 • 10
Conductor - Copper Solid Size Range	12-10
Conductor - Copper Str Aircraft Size	• AN 12 • AN 10
Conductor - Copper Str Aircraft Size Range	AN 12-AN 10
Conductor - Copper Str Navy Size	• 6 (7) • 6 (19) • 9 (7) • 9 (37)
Conductor - Copper Str Navy Size Range	6 (7)-9 (37)
Conductor Size	12 - 10 AWG
Conductor - Copper Str Size Range	12 AWG - 10 AWG
Conductor Type	• CU C Str-Size • CU C Solid-Size • CU C Str Aircraft-Size

Configuration

Connector Type	Seamless Butt Splice

Current

Voltage - Maximum	35000 V

Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Dimension - Outside Diameter inch	0.21 in
Dimension - L Length Overall mm	19 mm
Package Height	0.000 in
Dimension - Strip Length inch	5/16
Dimension - B Length fraction	5/16 in
Dimension - B Length inch	0.31 in
Dimension - Inside Diameter inch	0.13 in
Dimension - Length Overall inch	0.75 in

General

Die Index	36
Trade Name	HYLINK™
Sub Brand	HYLINK
Plated	Y
Feature - Barrel Style	Chamfered
Type	Splice
UPC 12 Digit	781810806050
UPC 14 Digit GTIN	00781810806050
Material	Copper
Plating Type	Tin
UPC	781810806050

Logistics

Minimum Pack Quantity	1000
Carton Quantity	1000
Pallet Quantity	99999

Operational

Temperature Rating	90

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved