YSM6C, Uninsulated Parallel Splice For 10,380 - 26,813 cmils



By Burndy
Catalog # YSM6C

Uninsulated Parallel Splice For 10,380 - 26,813 cmils

Features

- Seamless tubing
- Beveled barrel for ease of wire entry
- Tin plated
- Parallel design results in only one crimp necessary
- Uninsulated barrel provides an economical termination solution when insulation is not specified

Application

HYLINK Type YSM seamless parallel splice connector permits wires to be laid parallel inside the connector and spliced together with the BURNDY family of HYTOOL installation tooling

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - Industry Standards Met	UL486
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Buy America(n) Qualified	BABA Compliant (All status valid till December 2025)

Conductor

Conductor - Copper Solid Size	• 14 AWG • 13 AWG • 12 AWG
Conductor - Copper Solid Size Range	14 AWG-12 AWG
Conductor Size	10,380 - 26,813 cmils
Conductor - Copper Str Size	• 14 AWG • 12 AWG
Conductor - Copper Str Size Range	14 AWG-12 AWG
Conductor Type	• CU C Solid-Size • CU C Str-Size

Configuration

Connector Type	Parallel Splice

Dimensions

Dimension - Outside Diameter inch	0.31 in
Dimension - Strip Length inch	1/2
Dimension - Length Overall inch	0.44 in

General

Sub Brand	HYLINK
Trade Name	HYLINK™
Plated	Y
Feature - Barrel Style	Chamfered
Type	YSM
UPC 12 Digit	781810805787
UPC 14 Digit GTIN	00781810805787
Material	Copper
Plating Type	Tin
UPC	781810805787

Logistics

Minimum Pack Quantity	200
Carton Quantity	200

Operational

Temperature Rating	90

Product Assets

Catalog [English]

© 2025 Hubbell Incorporated. All rights reserved