YSM27, Uninsulated Parallel Splice For 133,650 - 167,332 cmils



By Burndy
Catalog # YSM27

Cu Uninsul Parallel Splice, Bvl Entry, 133650-167332 cmil Cable,197000-250000 cmil Sol Wire, 0.81" L, Tin Plated.

Features

- Seamless tubing
- Beveled barrel for ease of wire entry
- Tin plated
- Parallel design results in only one crimp necessary
- Uninsulated barrel provides an economical termination solution when insulation is not specified

Application

HYLINK Type YSM seamless parallel splice connector permits wires to be laid parallel inside the connector and spliced together with the BURNDY family of HYTOOL installation tooling

General

Catalog Number	YSM27
Connector Type	Parallel Splice
EU RoHS Indicator	Yes
Feature - Barrel Style	Chamfered
Material	Copper
Plated	Y
Plating Type	Tin
Sub Brand	HYLINK
Temperature Rating	90
Trade Name	HYLINK™
Type	YSM
UPC	781810807156
UPC 14 Digit GTIN	00781810807156

Dimensions

Dimension - Length Overall inch	0.81 in
Dimension - Outside Diameter inch	0.70 in
Dimension - Strip Length inch	7/8

Conductor Related

Conductor - Copper Str Size	2/0 AWG;3/0 AWG
Conductor - Copper Str Size Range	2/0 AWG-3/0 AWG
Conductor Size	133,650 - 167,332 cmils
Conductor Type	• CU C Solid-Size • CU C Str-Size

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	100
Minimum Pack Quantity	1
Pallet Quantity	46400

Product Assets

Catalogs - BURNDY Master Catalog - Section B - Small Terminals
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Customer Notices - Prop 65 Notice
Interactive Catalog - BURNDY Full-Line Digital Catalog
Sales Drawings - 50094200
Specifications - YSM27

©2025 Hubbell Incorporated. All rights reserved