SP14, Vinyl Splice For 16 - 14 AWG

By Burndy
Catalog # SP14

Vinyl Splice For 16 - 14 AWG



Features

- Manufactured from seamless electrolytic copper tubing to provide maximum conductivity and tensile strength in a high quality design with no seams to split
- Funnel entry for easy wire insertion
- Electro-tin plating provides durable, long lasting resistance to corrosion

Application

For Accommodating A Broad Range Of 600 Volt Cables

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - Industry Standards Met	UL486
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Copper Str Size	• 16 AWG • 14 AWG
Conductor - Copper Solid Size	• 16 AWG • 15 AWG • 14 AWG
Conductor - Copper Solid Size Range	16 AWG-14 AWG
Conductor Size	16 - 14 AWG
Conductor - Copper Str Size Range	16 - 14 AWG

Configuration

Connector Type	Seamless Butt Splice

Current

Voltage - Maximum	600 V

Dimensions

Dimension - Outside Diameter inch	0.18 in
Dimension - L Length Overall mm	25 mm
Dimension - Strip Length inch	1/4 in
Cable Insulation Diameter Maximum	0.180 in
Dimension - Length Overall inch	1.00 in
Dimension - Diameter Max Size inch	0.18 in

General

Insulation Type	Vinyl
Trade Name	VINYLINK™
Insulation	Y
Sub Brand	VINYLINK
Color Code	Blue
Plated	Y
Feature - Barrel Style	Shrouded
Type	SP
UPC 12 Digit	781810712016
UPC 14 Digit GTIN	00781810712016
Material	Copper
Plating Type	Tin
UPC	781810712016

Logistics

Minimum Pack Quantity	50
Carton Quantity	600
Pallet Quantity	99999

Operational

Temperature Rating	105° C

Product Assets

Catalog [English]

© 2025 Hubbell Incorporated. All rights reserved