Low Voltage Distribution Transformer - Three Phase, 480Δ - 208Y/120V, 15kVA

By Acme Electric
Catalog # T3533111S



Low Voltage Distribution Transformer - Three Phase, 480Δ - 208Y/120V, 15kVA

Features

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

Specifications

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 3R
UL Standard	UL 506
UL Insulation Class	180°C

Configuration

Electrostatic Shield	Shielded

Current

Frequency Rating	60 Hz
Primary Voltage	480D V
kVA	15.0
Primary Voltage	480Δ
Secondary Voltage	208Y/120 V

Dimensions

Length	9.03 in
Weight	250 lb.
Height	18.86 in
Width	20.3 in
Dimensions	9.03 in x 20.3 in x 18.86 in

General

Product Category	Dry Type Distribution Transformer
Material type	ZFIN
Taps % Steps	5.0%
Winding Material	AL
BNFC Taps	2
Mounting Type	Floor
UPC	047503733653
Construction	Encapsulated

Logistics

Pallet Quantity	4
Carton Quantity	1

Operational

Max Temperature Rise	115 Degrees Celsius

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved