KWIK-BRACE® Series with 1-1/2 in. Deep Box for New Construction, Two 1/2 in. KO's



By RACO
Catalog # 926

KWIK-BRACE® with 1-1/2 in. Deep Box for New Construction, Two 1/2 in. KO's

Features

- Slides apart to accommodate joist spacing from 16 in. to 24 in.
- Metal protection plate included
- Nail spurs for easy brace positioning
- #10-32, 1 in. long ceiling fan screws provided and #8-32 ceiling fixture mounting provisions
- Supplied with two 1/2 in. knockouts
- Easy installation, up front ground screw
- Easy to follow instructions and mounting hardware included

Specifications

Certified Listed	UL Listed
Buy American Compliant	Contact Manufacturer
EU RoHS Indicator	Contact Manufacturer
Buy America(n) Qualified	Contact Manufacturer

Configuration

Knockouts	1/2 in

Dimensions

Cubic Capacity	15.8 cu.in
Fixture Lbs., 16 in. Joist Span	210 lb.
Fixture Lbs., 24 in. Joist Span	90 lb.
Fixture Lbs.	90-210 lb.
Depth	1.5 in
Length	15.13 in
Size	4 in
Ceiling Fan Lbs., 16 in. Joist Span	70 lb.
Ceiling Fan Lbs., 24 in. Joist Span	70 lb.
Ceiling Fan Lbs.	70 lb.
Raised Ground	Yes
Width	4.25 in
Weight	2.333 lb.
Height	3.03 in
Dimensions	15.13 in x 4.25 in x 3.03 in

General

Series	KWIK-BRACE® Series
Fixture Type	• Ceiling • Light
Ceiling Fan Rated	Yes
Old Work or New Work	New Work
Type	Box
Material	Steel
Drawn or Welded	Drawn
UPC	050169009260

Logistics

Packaging Type	Box
Carton Quantity	6
Pallet Quantity	288

Product Assets

Catalog [English]
Catalog [English]
Catalog Page [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved