



Concrete Ring, Welded, 2-1/2 in. Deep, Single Row 1/2 & 3/4 in. KO's

By RACO
Catalog # 271

Concrete Ring, Welded, 2-1/2 in. Deep, Single Row 1/2 & 3/4 in. KO's

Features

- Single row of 1/2 in. and 3/4 in. knockouts
- Flat sides provide excellent contact for locknuts
- External ears are used to nail the concrete ring to the wood form
- Top cover is removable for before-pour work
- Waxed fixture ears prevent concrete from interfering with the threads
- Ears on inside of concrete ring are for fixtures
- Can support a light fixture up to 50 pounds
- 30.8 cu. in. capacity

Specifications

Certified Listed	UL Listed
Buy American Compliant	No
EU RoHS Indicator	Contact Manufacturer

Configuration

Knockouts	• 1/2 in • 3/4 in
-----------	---

Dimensions

Cubic Capacity	30.8 cu.in
----------------	------------



Fixture Lbs.	50 lb.
Depth	2.5 in
Actual Depth	2.779 in
Width	4 in
Weight	0.654 lb.
Height	4 in

General

Wiring System	Conduit
Color	Gray
Type	Concrete Ring
Material	Steel
Drawn or Welded	Welded
UPC	050169002711

Logistics

Packaging Type	No Packaging
Carton Quantity	25
Pallet Quantity	1500

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)