Concrete Ring, Welded, 6 in. Deep, Double Row 1/2 & 3/4 in. KO's

By RACO
Catalog # 276



Concrete Ring, Welded, 6 in. Deep, Double Row 1/2 & 3/4 in. KO's

Features

- Flat sides provide excellent contact for locknuts
- External ears are used to nail the ring to the wood form
- Top cover is removable for before-pour work
- Ears on inside of box are for fixtures
- Waxed fixture ears prevent concrete from interfering with the threads
- A variety of covers are available
- Cover plate must be orered separately with all RACO® concrete rings

Specifications

Certified Listed	UL Listed
Buy American Compliant	No
EU RoHS Indicator	Contact Manufacturer

Configuration

Knockouts	• 1/2 in • 3/4 in

Dimensions

Cubic Capacity	74.0 cu.in
Fixture Lbs.	50 lb.
Depth	6 in
Width	4 in
Weight	1.57 lb.
Height	4 in

General

Wiring System	Conduit
Type	Concrete Ring
Material	Steel
Drawn or Welded	Welded
UPC	050169002766

Logistics

Packaging Type	No Packaging
Carton Quantity	10
Pallet Quantity	600

Product Assets

Catalog [English]
Catalog [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved