# Concrete Ring, Welded, 4 in. Deep, Double Row 1/2 & 3/4 in. KO's

By RACO
Catalog # 274



Concrete Ring, Welded, 4 in. Deep, Double Row 1/2 & 3/4 in. KO's

## Features

- Flat sides provide excellent contact for locknuts
- External ears are used to nail the ring to the wood form
- Top cover is removable for before-pour work
- Ears on inside of box are for fixtures
- Waxed fixture ears prevent concrete from interfering with the threads
- A variety of covers are available
- Cover plate must be orered separately with all RACO® concrete rings
- Used in high-rise construction
- 61.5 cu. in. capacity
- Not designed for ceiling fan support, the maximum support load for a static fixture is 50 lbs

## Specifications

| | |
|---|---|
| Certified Listed | UL Listed |
| Buy American Compliant | No |
| EU RoHS Indicator | Contact Manufacturer |

## Configuration

| | |
|---|---|
| Knockouts | • 1/2 in<br>• 3/4 in |

## Dimensions

| | |
|---|---|
| Cubic Capacity | 49.3 cu.in |
| Fixture Lbs. | 50 lb. |
| Depth | 4 in |
| Width | 4 in |
| Weight | 1.03 lb. |
| Height | 4 in |

## General

| | |
|---|---|
| Wiring System | Conduit |
| Color | Gray |
| Type | Concrete Ring |
| Material | Steel |
| Drawn or Welded | Welded |
| UPC | 050169002742 |

## Logistics

| | |
|---|---|
| Packaging Type | No Packaging |
| Carton Quantity | 20 |
| Pallet Quantity | 1000 |

## Product Assets

Catalog [English]
Catalog [English]
Catalog Page [English]
Customer Drawing [English]



© 2026 Hubbell Incorporated. All rights reserved