Concrete Ring, Welded, 3-1/2 in. Deep, Single Row 3/4 in. & 1 in. KO's

By RACO
Catalog # 278



Concrete Ring, Welded, 3-1/2 in. Deep, Single Row 3/4 in. & 1 in. KO's

Features

- Flat sides provide excellent contact for locknuts
- External ears are used to nail the ring to the wood form
- Top cover is removable for before-pour work
- Ears on inside of box are for fixtures
- Waxed fixture ears prevent concrete from interfering with the threads
- A variety of covers are available
- Cover plate must be orered separately with all RACO® concrete rings

Specifications

Certified Listed	UL Listed
Buy American Compliant	No
EU RoHS Indicator	Contact Manufacturer

Configuration

Knockouts	• 3/4 in • 1 in

Dimensions

Cubic Capacity	43.0 cu.in
Fixture Lbs.	50 lb.
Depth	3.5 in
Width	4 in
Weight	0.906 lb.
Height	4 in

General

Wiring System	Conduit
Type	Concrete Ring
Material	Steel
Drawn or Welded	Welded
UPC	050169002780

Logistics

Packaging Type	No Packaging
Carton Quantity	20
Pallet Quantity	1000

Product Assets

Catalog [English]
Catalog [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved