4 in. x 2 in. Handy Box, Welded, 2-1/8 in. Deep, Eight 1/2 in. KO's, TS Bracket

By RACO
Catalog # 678



4 in. x 2 in. Handy Box, Welded, 2-1/8 in. Deep, Eight 1/2 in. KO's, TS Bracket

Features

- Constructed of pre-galvanized steel with "TS" side-mount bracket
- 4 in. x 2 in., 2-1/8 in. deep
- With proper fitting can be used for conduit, NMSC, armored, metal clad, flex cable
- Supplied with eight 1/2 in. knockouts
- 16.5 cu. in. capacity
- Acceptable for use in 2-hour fire rated walls

Specifications

Certified Listed	UL Listed
Buy American Compliant	Contact Manufacturer

Configuration

Knockouts	1/2 in
Bracket Type	TS, for Metal or Wood Studs
Bracket Setback	0.50
Number of Gang(s)	1-Gang

Current

Power Distribution Features	Fire Rated

Dimensions

Cubic Capacity	16.5 cu.in
Depth	2.125 in
Actual Depth	2.188 in
Raised Ground	No
Width	2.375 in
Weight	0.735 lb.
Height	7 in

General

Wiring System	Conduit
Color	Gray
Type	Box
Fire Resistance	Yes
Material	Steel
Drawn or Welded	Welded
UPC	050169006788

Logistics

Packaging Type	No Packaging
Carton Quantity	25
Pallet Quantity	1500

Product Assets

Catalog [English]
Catalog [English]
Catalog Page [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved