1/2 in. Hubs Form 1 Liquidtight Strain Relief Connector, Cable Range .187 - .250



By RACO
Catalog # 4801-2

1/2 in. Hubs Form 1 Liquidtight Strain Relief Connector, Cable Range .187 - .250

Features

- Aluminum construction provides a corrosion resistant installation
- Innovative GOTHCA® ring incorporates a split hinge design to prevent friction and to provide strain relief
- Neoprene grommet
- Knurled compression nut allows the fittings to be hand tightened to UL requirements
- GOTCHA® color-coded ring provides fast identification of cord size
- Additional colors and sizes available

Specifications

Certified Listed	• UL Listed • CSA Certified
Buy American Compliant	Contact Manufacturer
Environmental Conditions	Wet Location
EU RoHS Indicator	Contact Manufacturer
Hazardous Rating(s)	• Class I, Division 2 • Class II Division 1 & 2 • Class III, Division 1 & 2
Industry Standard(s)	UL 514B
Buy America(n) Qualified	Contact Manufacturer

Conductor

Cable Range	.187 - .250 in

Configuration

Connector Type	Strain-Relief

Dimensions

Form Size	1 in
Trade Size	1/2 in
Length	0.88 in
Width	1.36 in
Weight	0.059 lb.
Height	1.36 in
Dimensions	0.88 in x 1.36 in x 1.36 in

General

Fitting Type	Connectors
Color Code	Red
Conduit Type	Liquidtight
Material	Aluminum
UPC	050169480120

Logistics

Minimum Pack Quantity	25
Carton Quantity	25
Pallet Quantity	12000

Product Assets

Catalog [English]
Catalog [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved