3/4 in. Hubs Form 2 Liquidtight Strain Relief Connector, Cable Range .250 - .375

By Raco
Catalog # 4803-3



*Representative Image

3/4 in. Hubs Form 2 Liquidtight Strain Relief Connector, Cable Range .250 - .375

Features

- Aluminum construction provides a corrosion resistant installation
- Innovative GOTHCA® ring incorporates a split hinge design to prevent friction and to provide strain relief
- Neoprene grommet
- Knurled compression nut allows the fittings to be hand tightened to UL requirements
- GOTCHA® color-coded ring provides fast identification of cord size
- Additional colors and sizes available

General

Catalog Number	4803-3
Color Code	White
Conduit Type	Liquidtight
Connector Type	Strain-Relief
EU RoHS Indicator	Contact Manufacturer
Environmental Conditions	Wet Location
Fitting Type	Connectors
Material	Aluminum
UPC	050169480335

Dimensions

Dimensions	2.05 in x 1.13 in x 1.13 in
Form Size	2 in
Height	1.13 in
Length	2.05 in
Trade Size	3/4 in
Weight	0.117 lb
Width	1.13 in

Conductor Related

Cable Range	0.250 - 0.375 in

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Certified Listed	• UL Listed • CSA Certified
Hazardous Rating(s)	• Class I, Division 2 • Class II Division 1 & 2 • Class III, Division 1 & 2
Industry Standard(s)	UL 514B

Logistics

Carton Quantity	25
Minimum Pack Quantity	25
Pallet Quantity	7600

Product Assets

Catalogs - RACO / TayMac / Bell Full Catalog
Catalogs - Commercial Fittings
Literature - Raco_Liquidtight_Diameter_Range_B60
Product Logo - LT CORD
SDS - HCC SDS
Specifications - 48033
Terms and Conditions - HCC Terms & Conditions

©2025 Hubbell Incorporated. All rights reserved