# 1/2 in. Service Entrance Liquidtight UF Connector

By RACO
Catalog # 4899-9

1/2 in. Service Entrance Liquidtight UF Connector



## Features

- Rugged metallic construction will last the life of the installation.
- Grommet opening min: .20 in. x .40 in. max, .25 in. x .55 in
- Aluminum body construction will last the lifetime of the installation
- 1/2 in. trade size: 2 #14, 2 #12, 2#10 UF wire
- UL and CSA listed

## Specifications

| | |
|---|---|
| Certified Listed | • UL Listed<br>• CSA Certified |
| Buy American Compliant | Contact Manufacturer |
| EU RoHS Indicator | Contact Manufacturer |
| Industry Standard(s) | UL 514B |
| Buy America(n) Qualified | Contact Manufacturer |

## Dimensions

| | |
|---|---|
| Trade Size | 1/2 in |
| Length | 1.65 in |
| Grommet Opening Maximum | .25 x .55 in |
| Grommet Opening Minimum | .20 x .40 in |
| Width | 1.25 in |
| Weight | 0.087 lb. |
| Height | 1.25 in |
| Dimensions | 1.65 in x 1.25 in x 1.25 in |

## General

| | |
|---|---|
| Fitting Type | Connectors |
| Conduit Type | Service Entrance |
| Accessory Type | Fitting |
| Material | Aluminum |
| UPC | 050169489994 |

## Logistics

| | |
|---|---|
| Minimum Pack Quantity | 10 |
| Carton Quantity | 10 |
| Pallet Quantity | 4800 |

## Product Assets

Catalog [English]
Catalog [English]
Catalog Page [English]
Catalog Page [English]



© 2026 Hubbell Incorporated. All rights reserved