1/2 in. Hubs - Form 1 Liquidtight Strain Relief Cord Connector, Cable Range .250 - .375



By RACO
Catalog # 3702-2

1/2 in. Hubs - Form 1 Liquidtight Strain Relief Cord Connector, Cable Range .250 - .375

Features

- All steel/malleable construction provides mechanical strength
- Unique Neoprene grommet design - grommet is forced up and around the cord when the nut is tightened for a positive liquidtight seal
- Washers have size range imprinted for identification - eliminates misidentifying inventory
- Use RACO locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel
- All metallic components are zinc electroplated for corrosion protection
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code and packaged in pre-scored tear top cartons for an attractive presentation
- 3/8 in. to 1 in. Steel, 1-1/4 in. to 1-1/2 in. Malleable Iron bodies and nuts
- Additional sizes available

Specifications

Buy American Compliant	Contact Manufacturer
Environmental Conditions	Wet Location
EU RoHS Indicator	Contact Manufacturer
Hazardous Rating(s)	• Class I, Division 2 • Class II Division 1 & 2 • Class III, Division 1 & 2
Buy America(n) Qualified	Contact Manufacturer

Conductor

Cable Range	0.250 - 0.375 in

Configuration

Connector Type	Strain-Relief

Dimensions

Form Size	1 in
Trade Size	1/2 in
Length	1.453 in
Width	1.063 in
Weight	0.174 lb.
Height	1.063 in
Dimensions	1.453 in x 1.063 in x 1.063 in

General

Fitting Type	Connectors
Conduit Type	Liquidtight
Accessory Type	Fitting
Material	Steel/Malleable Iron
UPC	050169370223

Logistics

Minimum Pack Quantity	25
Carton Quantity	25
Pallet Quantity	12000

Product Assets

Catalog [English]
Catalog [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved