# 3/4 in. Hubs - Form 3 Liquidtight Strain Relief Cord Connector, Cable Range .600 - .650



By RACO
Catalog # 3703-4

3/4 in. Hubs - Form 3 Liquidtight Strain Relief Cord Connector, Cable Range .600 - .650

## Features

- All steel/malleable construction provides mechanical strength
- Unique Neoprene grommet design - grommet is forced up and around the cord when the nut is tightened for a positive liquidtight seal
- Washers have size range imprinted for identification - eliminates misidentifying inventory
- Use RACO locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel
- All metallic components are zinc electroplated for corrosion protection
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code and packaged in pre-scored tear top cartons for an attractive presentation
- 3/8 in. to 1 in. Steel, 1-1/4 in. to 1-1/2 in. Malleable Iron bodies and nuts
- Additional sizes available

## Specifications

| | |
|---|---|
| Buy American Compliant | Contact Manufacturer |
| Environmental Conditions | Wet Location |
| EU RoHS Indicator | Contact Manufacturer |
| Hazardous Rating(s) | • Class I, Division 2<br>• Class II Division 1 & 2<br>• Class III, Division 1 & 2 |
| Buy America(n) Qualified | Contact Manufacturer |

## Conductor

| | |
|---|---|
| Cable Range | .600 - .650 in |

## Configuration

| | |
|---|---|
| Connector Type | Strain-Relief |

## Dimensions

| | |
|---|---|
| Form Size | 3 in |
| Trade Size | 3/4 in |
| Length | 1.484 in |
| Width | 1.406 in |
| Weight | 0.196 lb. |
| Height | 1.406 in |
| Dimensions | 1.484 in x 1.406 in x 1.406 in |

## General

| | |
|---|---|
| Fitting Type | Connectors |
| Conduit Type | Liquidtight |
| Material | Steel/Malleable Iron |
| UPC | 050169370346 |

## Logistics

| | |
|---|---|
| Minimum Pack Quantity | 25 |
| Carton Quantity | 25 |
| Pallet Quantity | 7600 |

## Product Assets

Catalog [English]
Catalog [English]
Catalog Page [English]



© 2026 Hubbell Incorporated. All rights reserved