3/4 in. Hubs - Form 3 90 Degree Liquidtight Strain Relief Cord Connector, Cable Range .600 - .650



By RACO
Catalog # 3793-4

3/4 in. Hubs - Form 3 90 Degree Liquidtight Strain Relief Cord Connector, Cable Range .600 - .650

Features

- All steel/malleable construction provides mechanical strength
- Unique Neoprene grommet design - grommet is forced up and around the cord when the nut is tightened for a positive liquidtight seal
- Washers have size range imprinted for indentification - eliminates misidentifying inventory
- Use RACO locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel
- All metallic components are zinc electroplated for corrosion protection
- 1/2 in. to 3/4 in. Malleable Iron bodies
- 1/2 in. to 3/4 in. Steel nuts
- Additional sizes available

Specifications

Certified Listed	cULus Listed
Buy American Compliant	Contact Manufacturer
Environmental Conditions	Wet Location
EU RoHS Indicator	Contact Manufacturer
Hazardous Rating(s)	• Class I, Division 2 • Class II Division 1 & 2 • Class III, Division 1 & 2
Buy America(n) Qualified	Contact Manufacturer

Conductor

Cable Range	.600 - .650 in

Configuration

Connector Type	Strain-Relief

Dimensions

Form Size	3 in
Trade Size	3/4 in
Length	2.375 in
Width	1.204 in
Weight	0.381 lb.
Height	2.227 in
Dimensions	2.375 in x 1.204 in x 2.227 in

General

Fitting Type	Connectors
Conduit Type	Liquidtight
Material	Malleable Iron
UPC	050169379349

Logistics

Minimum Pack Quantity	10
Carton Quantity	10
Pallet Quantity	4800

Product Assets

Catalog [English]
Catalog [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved