1 in. 45 Degree Liquidtight Connector, Uninsulated

By RACO
Catalog # 3444

1 in. 45 Degree Liquidtight Connector, Uninsulated



Features

- Use with flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Zinc-electroplated for added corrosion protection
- Noninsulated
- Innovative split gland-ring assures a perfect seal, preventing pullouts
- Available in trade sizes 3/8 in. through 4 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

Specifications

Certified Listed	• UL Listed • CSA Certified
Buy American Compliant	Contact Manufacturer
Environmental Conditions	Wet Location
EU RoHS Indicator	Yes
Hazardous Rating(s)	• Class I, Division 2 • Class II Division 1 & 2 • Class III, Division 1 & 2
Industry Standard(s)	UL 514B
Buy America(n) Qualified	Contact Manufacturer

Dimensions

Trade Size	1 in
Length	1.938 in
Width	1.938 in
Weight	0.535 lb.
Height	3.375 in
Dimensions	1.938 in x 1.938 in x 3.375 in

General

Fitting Type	Connectors
Insulation Type	Uninsulated
Conduit Type	Liquidtight
Material	Steel/Malleable Iron
UPC	050169034446

Logistics

Minimum Pack Quantity	10
Carton Quantity	10
Pallet Quantity	3200

Product Assets

Catalog [English]
Catalog [English]
Catalog Page [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved