BURNDY

YA38LTC38FX, Compression Terminal, 500 kcmil H,I,K, 550 kcmil G,H,I, 535 DLO, Cu, 1-Hole, 3/8" Stud, Standard Barrel



By Burndy
Catalog # YA38LTC38FX

500 kcmil H,I,K / 550 kcmil G,H,I,535 DLO, CU, 1 Hole, 3/8 Stud, Standard Barrel, Inspection Window

Features

- Barrel designed with internal chamfer at wire entry for smooth insertion of wire, preventing possible damage of the strands
- Standard barrel length is recommended for installations with limited space availability
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding

Application

Wire Termination

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	500-550 KCMIL
Conductor - Copper Str Size	500-550 KCMIL
Conductor - Copper Flex I Size Range	500 / 550 kcmil
Conductor - Copper Flex K Size	500 KCMIL
Conductor - Copper Flex K Size Range	500 kcmil
Conductor - Copper Flex M Size	500 kcmil
Conductor - Copper Flex M Size Range	500 kcmil
Conductor - Copper DLO Size	535 KCMIL
Conductor - Copper DLO Size Range	535 kcmil
Conductor - Copper Flex G Size	550 KCMIL
Conductor - Copper Flex G Size Range	550 kcmil
Conductor - Copper Flex H Size	500-550 KCMIL
Conductor Size	500-550 KCMIL
Conductor - Copper Str Size Range	500 / 550 kcmil
Conductor - Copper Flex H Size Range	500 / 550 kcmil
Conductor Type	FLEX
Conductor - Copper Flex I Size	500-550 KCMIL

Configuration

Physical Attribute - Number of Holes	1
Connector Type	STANDARD BARREL

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - Outside Diameter inch	1.25 in
Dimension - L Length Overall mm	85 mm
Dimension - Pad Width inch	1.84 in
Dimension - Height mm	0 mm
Dimension - Hole Size fraction	3/8
Dimension - Hole Size inch	0.41
Dimension - Hole Size mm	10.4 mm
Dimension - Strip Length inch	1-7/16
Dimension - Stud Size fraction	3/8
Dimension - Stud Size inch	3/8
Dimension - B Length fraction	1-7/16 in
Dimension - B Length inch	1.45 in
Dimension - Z inch	0.52 in
Physical Attribute - Tongue Angle	Straight
Dimension - Bolt Hole Size inch	0.39 in
Dimension - Bolt Size fraction	3/8
Dimension - Bolt Size inch	0.38
Dimension - Length Overall inch	3.34 in
Dimension - N inch	0.50 in

General

Die Index	L99
Trade Name	HYLUG™
Sub Brand	HYLUG
Color Code	Pink
Plated	Y
Feature - Barrel Type	Standard
Feature - Barrel Style	Chamfered
Type	Standard Barrel, Tin Plated
UPC 12 Digit	781810156391
UPC 14 Digit GTIN	00781810156391
Material	COPPER
Plating Type	Tin
Finish Type	Tin-Plated
UPC	781810156391

Logistics

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	3700

Product Assets

Catalog [English]
Installation Manual [English]
Installation Manual [English]

A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved