1PL2/03, UV Rated Black, 1-Sided, 3-Port, #14-2/0 AWG



By Burndy
Catalog # 1PL2/03

UV Rated Covering, Oxide inhibitor pre-installed, Same-Side, 3-Port Tap, #14-2/0 AWG

Features

- UV Rated Covering over AL6061-T6 aluminum body saves time, lowering installation costs and eliminates taping
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces the number of connectors necessary to carry in inventory

Application

For Indoor Use Only, Copper Or Stranded Aluminum

Specifications

Certification - UL Recognized	No
Buy American Compliant	Contact Manufacturer
Certification - cULus	No
Buy America(n) Qualified	Buy America Compliant (All status valid till December 2026)
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	No

Conductor

Conductor - AL Str Size	• 14 AWG • 12 AWG • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 • 2/0 AWG
Conductor - AL Str Size Range	14 AWG - 2/0 AWG
Conductor - Copper Str Size	• 14 AWG • 12 AWG • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 • 2/0 AWG
Conductor Size	14-2/0 AWG
Conductor Type	• AL C Str-Size • CU C Str-Size
Conductor - Copper Str Size Range	14 AWG - 2/0 AWG

Configuration

Physical Attribute - Number of Screws	3
Number Of Ports	3
Connector Type	Multi Tap

Current

Voltage - Maximum	600 V

Dimensions

Package Height	0.000 in
Dimension - Height mm	35.1 mm
Dimension - Height inch	1.38 in
Dimension - Height fraction	1.375 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	56 mm
Width	1.31 in
Dimension - Width fraction	1-31/100 in
Dimension - Screw Size inch	7/16
Length	2.19 in
Dimension - Width mm	33 mm
Dimension - Width inch	1.31 in
Height	1.38 in
Dimension - Length Overall inch	2.19 in
Dimensions	2.19 in x 1.31 in x 1.38 in

Force Related

Installation Torque Recommended in-lb	120 in-lb

General

Product Family	MECHANICAL
Insulation Type	Plastisol
Trade Name	UNITAP™
Material - Hardware	Aluminum
Insulation	Y
Plated	No
Sub Brand	UNITAP
Product Type	Run/Tap
UPC	781810286845
Type	BIBS, Multi-Port
Hex Key	3/16
Material	Aluminum
Plating Type	Unplated
UPC 12 Digit	781810286845
UPC 14 Digit GTIN	00781810286845

Logistics

Minimum Pack Quantity	1
Pallet Quantity	6400
Carton Quantity	100

Operational

Temperature Rating	194° F

Product Assets

Catalog [English]
Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved