HUBBELL
Premise Wiring

PROClick Connector, SC/APC, OM1, Green, 12 Pack

By Hubbell Premise Wiring
Catalog # FCSC900KASM12



Fiber Optic Connectors, ProClick SC/APC, Singlemode, Pre-Polished, 10GHz, 900, 12 Pack.

Features

- Terminate in Less than 60 Seconds
- RoHS Compliant and Bulk Packed in Recyclable Cartons

Application

Interconnect

Performance

- Optical - Insertion loss - 0.5dB (0.35dB typical), 0.75dB max
- Optical - Mating durability - 500 cycles <
- 0.1dB change
- Optical - Multimode return loss - 35dB Typ, 22dB minimum
- Optical - Singlemode return loss - 55dB Typ, 40dB minimum
- Environmental - Operating temperature - 0 ºC to +70 ºC

General

Adapter Type	SC
Catalog Number	FCSC900KASM12
Color	Green
Connector Type	SC
EU RoHS Indicator	Yes
Enclosure Type	Various
Environmental Conditions	Indoor
Item Type	SC
Material	Ceramic
Material - Mounting Hardware	Fiber Termination, No Polish
OEM Brand Name	Hubbell Premise Wiring
Repeatability	0.1 dB
Service Life	500 matings
Specifications	• Cable Type - 900/250 QM • Ferrule Material - Zirconia ceramic, UPC polish • Fiber Type - APC SM, OS2
Style	PROclick
Sub Brand	OptiChannel
Temperature Rating	0C to 70C
UPC	662620224114

Dimensions

Display Size	2.5 mm

Electrical Ratings

Connectivity	Fiber Optic Connector
Insertion Loss	0.75 dB Max
Return Loss	26

Conductor Related

Fiber Size	125 Micron
Fiber Type	APC, OS2, SM

Certifications And Compliance

Industry Standard(s)	• Telcordia GR-326-CORE • TIA-568-C.3 • TIA-604-FOCIS

Logistics

Carton Quantity	10

Product Assets

Brochures - Fiber Connectivity Product Guide
Case Studies - CASE STUDY | SHIPBOARD NETWORKS
Catalog Page - PREM G3 CatalogPage
Catalog Page - PREM G03 Catalog Page
Catalog Page - PREM G20 Catalog Page
Catalogs - Premise Wiring Catalog
Literature - FIBERHUBB PROclick® Fiber Connectors
Literature - FIBERHUBB™ Passive Optical LAN (POL) Solution
Literature - PROclick® Fiber Connectors
Sales Drawings - FCSC900K - PDF
Specifications - FCSC900KASM12

©2025 Hubbell Incorporated. All rights reserved