HUBBELL
Premise Wiring

HFCD14 Series Indoor/Outdoor Tight Buffer, 12 strand, I/O Tight Buffer Riser, OM4, MM, Black Jacket



By Hubbell Premise Wiring
Catalog # HFCD14012R4BK

HFCD14 Series Indoor/Outdoor Tight Buffer, 12 strand, I/O Tight Buffer Riser, OM4, MM , Black Jacket.

Application

Data Tranmission

General

Attenuation	3.5/1.5 Db per Kilometer
Bandwidth	4000 bps
Cable Rating	I/O Tight Buffer Riser
Catalog Number	HFCD14012R4BK
Color	Black
Material - Jacket	PVC
Sub Brand	Fiber Optics
Temperature Rating	-20 Degrees C to 70 Degrees C
Type	Cable
UPC	662620333878

Electrical Ratings

Wavelength	850/1300 Nanometers

Conductor Related

Fiber Size	OM4
Fiber Type	OM4, MM
Number of Fibers	12

Certifications And Compliance

Industry Standard(s)

- ANSI/ICEA S-83-596
- NFPA-262/UL910/CSA FT-4
- Telcordia GR-409 and GR-20
- TIA-568.3-D

Product Assets

Catalog Page - PREM I04 Catalog Page
Catalog Page - PREM I4 CatalogPage
Catalogs - Premise Wiring Catalog
Literature - Fiber Optic Cable Guide
Specifications - HFCD14012R4BK

©2025 Hubbell Incorporated. All rights reserved