
Y3129R, Compression Splice Reducer Adapter, Cu



By Burndy
Catalog # Y3129R

Copper Reducing Adapter for 350 kcmil down to 250 kcmil, Tin Plated, for use with Long Barrel Splices (not included)

Features

- Copper reducing sleeve that allows a larger terminal or splice to accommodate a smaller wire gauge

Application

Wire Reducing Splice Adapter Insert

Specifications

Certification - ETL	No
Certification - UL Recognized	No
Standards - RoHS Compliance Status	CM
Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Buy America(n) Qualified	Contact Manufacturer
UL Listed	No
Certification - CSA Approved	No

Conductor

Conductor - Copper Str Run Range	350 kcmil
Conductor - Copper Str Run	350 kcmil
Conductor - Material	COPPER
Wire Size	250 kcmil
Conductor Type	CODE
Conductor - Copper Str Size Range	250 kcmil
Conductor - Copper Str Tap Range	250 kcmil
Conductor - Copper Str Tap	250 KCMIL

Configuration

Connector Type	LONG BARREL

Current

Voltage - Maximum	35000

Dimensions

Package Height	0.000 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	51 mm
Dimension - B Length inch	2.00 in
Dimension - Outside Diameter inch	0.687 in
Dimension - Length Overall inch	2.00 in

General

Feature - Barrel Type	Long
Plated	Y
Color Code	Red
Sub Brand	REDUCER SPLICES
Die Index	18
UPC	781810081938
Type	Y-R
Material	Copper
Plating Type	Tin Plated
Finish Type	Tin-Plated
UPC 12 Digit	781810081938
UPC 14 Digit GTIN	00781810081938

Logistics

Minimum Pack Quantity	1
Pallet Quantity	46400
Carton Quantity	100

Operational

Temperature Rating	194

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved