HUBBELL
Premise Wiring

HFCD15 Series Indoor Tight Buffer Distribution, 24 strand, Plenum, Armored, OS2, SM, Yellow Jacket



By Hubbell Premise Wiring
Catalog # HFCD15024PS

HFCD15 Series Indoor Tight Buffer Distribution, 24 strand, Plenum, Armored, OS2, SM , Yellow Jacket.

Application

Data Tranmission

General

Attenuation	0.5/0.4 Db per Kilometer
Cable Rating	Plenum, Armored
Catalog Number	HFCD15024PS
Color	Yellow
Material - Jacket	PVC
Specifications	• Armor - Aluminum Interlock • Cable Diameter in (mm) - 0.69 (17.4) • Cable Weight (lb/kft) - 188 • Construction - Single Unit, Aramid Strength Member • Fiber Coating - 900 Micron PVC Tight Buffer
Sub Brand	Fiber Optics
Temperature Rating	0 Degrees C to 70 Degrees C
Type	Cable
UPC	662620326559

Electrical Ratings

Wavelength	1310/1550 Nanometers

Conductor Related

Fiber Size	OS2
Fiber Type	OS2, SM
Number of Fibers	24

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
Industry Standard(s)	• ANSI/ICEA S-83-596 • NFPA-262/UL910/CSA FT-6 • Telcordia GR-409 • TIA-568.3-D

Product Assets

Catalog Page - PREM I03 Catalog Page
Catalog Page - PREM I3 CatalogPage
Catalogs - Premise Wiring Catalog
Literature - Fiber Optic Cable Guide
Specifications - HFCD15024PS

©2025 Hubbell Incorporated. All rights reserved