HUBBELL
Premise Wiring

HFCD15 Series Indoor Tight Buffer Distribution, 12 strand, Plenum, Armored, OM4, MM, Aqua Jacket

By Hubbell Premise Wiring
Catalog # HFCD15012P4



Features

-
-
-
-

Application

Data Tranmission

General

Attenuation	3.5/1.5 Db per Kilometer
Bandwidth	4000 bps
Cable Rating	Plenum, Armored
Catalog Number	HFCD15012P4
Color	Aqua
Material - Jacket	PVC
Specifications	• Armor - Aluminum Interlock • Cable Diameter in (mm) - 0.63 (16) • Cable Weight (lb/kft) - 170 • Construction - Single Unit, Aramid Strength Member • Fiber Coating - 900 Micron PVC Tight Buffer
Sub Brand	Fiber Optics
Temperature Rating	0 Degrees C to 70 Degrees C
Type	Cable
UPC	662620332116

Electrical Ratings

Wavelength	850/1300 Nanometers

Conductor Related

Fiber Size	OM4
Fiber Type	OM4, MM
Number of Fibers	12

Certifications And Compliance

Buy America(n) Qualified	Buy American Act Compliant (All status valid till December 2024)
Industry Standard(s)	• ANSI/ICEA S-83-596 • NFPA-262/UL910/CSA FT-6 • Telcordia GR-409 • TIA-568.3-D

Product Assets

Catalog Page - PREM I03 Catalog Page
Catalog Page - PREM I3 CatalogPage
Catalogs - Premise Wiring Catalog
Literature - Quick Turn Custom Fiber Trunk Assemblies Program
Literature - Fiber Optic Cable Guide
Literature - Cut to Length Fiber Cable
Specifications - HFCD15012P4

©2025 Hubbell Incorporated. All rights reserved