Low Voltage Distribution Transformer - Single Phase, 277/480 - 208/277V, 10kVA

By Acme Electric
Catalog # GP1210000S

Low Voltage Distribution Transformer - Single Phase, 277/480 - 208/277V, 10kVA

Features

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

Specifications

Buy American Compliant	Contact Manufacturer
CSA Standard	C22.2 No. 47
UL Insulation Class	180°C
Nema Rating	NEMA 3R
UL Standard	UL 506
Buy America(n) Qualified	Contact Manufacturer

Configuration

Electrostatic Shield	Shielded

Current

Frequency Rating	60 Hz
kVA	10.0
Primary Voltage	277/480 V
Secondary Voltage	208/277 V
Primary Voltage	277/480

Dimensions

Length	10.84 in
Width	13.5 in
Weight	125 lb.
Height	15.19 in
Dimensions	10.84 in x 13.5 in x 15.19 in

General

Winding Material	AL
Material type	ZFIN
Product Category	Dry Type Distribution Transformer
Construction	Encapsulated
UPC	047503001073
Mounting Type	Wall

Logistics

Carton Quantity	1
Pallet Quantity	6

Operational

Max Temperature Rise	115 Degrees Celsius

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved