YGHHC29C26 Compression Grounding C-TAP Connector



By Burndy
Catalog # YGHHC29C26

Compression ground connector, Material: Copper, Range Run: 3/0 Str-250 kcmil, 1/2" or 5/8" Rod; Tap: #6 sol-2/0 Str.

Features

- Double Figure C Connector, C-Shaped opening permits two continuous parallel cables into conductor groove
- Qualified to IEEE-837 2014
- Prefilled with PENETROX compound and strip sealed

Application

For Direct Burial cables

Specifications

Standards - Industry Standards Met	• UL467 • IEEE 837 • IEEE 837 2014 Qualified • UL 486A-486B
Standards - RoHS Compliance Status	CM
EU RoHS Indicator	Contact Manufacturer
Certification - UL Listed Direct Burial	Yes
Industry Standard(s)	• UL 467 • IEEE 837 • IEEE 837 2014 Qualified • UL 486A-486B
Certification - CSA Approved	[Delete]

Conductor

Conductor - Rod Run Range	1/2" or 5/8" Rod
Conductor - Copper Str Run Range	3/0 Stranded - 250 kcmil
Conductor - Copper Solid Tap Range	6 Solid - 2/0 Solid
Conductor - Copper Str Tap Range	6 Stranded - 2/0 Stranded

Configuration

Connector Type	Tap

Dimensions

Package Height	0.000 in
Dimension - Height mm	0 mm
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in

General

Plated	N
Trade Name	HYTAP™
Sub Brand	HYTAP
Die Index	997
UPC	621945456235
Type	Taps
Material	Copper
UPC 12 Digit	621945456235
UPC 14 Digit GTIN	00621945456235

Logistics

Pallet Quantity	3600
Carton Quantity	15

Product Assets

Catalog [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved