3/8 in. Armored Cable Connector, .402-.610

By RACO
Catalog # 38RAC

3/8 in. Armored Cable Connector, .402-.610



Features

- Fits standard 1/2" knockouts in electrical boxes or enclosures
- Connector designed to terminate MC-PCS, MCI, MCI-A, AC, HCF, and FMC
- Die-cast zinc construction with nylon anti-short bushing
- For use in dry locations
- See Sell Sheet for cable ranges

Specifications

Certified Listed	cULus Listed

Conductor

Cable Range	0.402 - 0.610

Dimensions

Weight	0.066 lb.
Height	0.992 in
Width	0.948 in
Package Height	4.120 in
Length	1.471 in
Package Weight	0.355 lb.
Package Length	7.440 in
Package Width	4.580 in
Dimensions	1.471 in x 0.948 in x 0.992 in

General

Conduit Type	Armored Cable/Metal Clad (AC/MC)
UPC	050169000380
Material	Die Cast Zinc
Fitting Type	Connectors

Logistics

Minimum Pack Quantity	50
Pallet Quantity	16000
Carton Quantity	500

Product Assets

Catalog [English]
Catalog [English]
Catalog Page [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved