HUBBELL
Wiring Device-Kellems



By Hubbell Wiring Device-Kellems
Catalog # USB15X2W

Straight Blade Devices, Receptacles, Duplex, Dual USB Type 2.0 ports 3.8 Amp, 5 Volt DC, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, White

Application

USB Charger Hospital Grade

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Flammability - UL 94V-2
- Environmental - Operating Temperature - Maximum continuous 75°C, minimum -40°C (w/o impact)
- Mechanical - Product Identification - Ratings are a permanent part of the device
- Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA
- Mechanical - USB Port - Stainless steel Rated for 10,000 plug insertions and removal

General

Catalog Number	USB15X2W
Color	White
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Horsepower - Maximum	0.5
Indicator(s) Type	Green LED
Item Type	USB Charger Decorator Duplex
Material	Thermoplastic
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Series	Heavy Duty
Specifications	• Base - RTP • Clamp - Plated steel • Contacts - Plated steel • Face - RTP • LED - Green Indicator • Mounting Screws - Zinc plated steel • Mounting Strap - .040" Zinc plated steel • Terminal Screws - Plated steel • USB Port - Stainless Steel
Style	Style Line Decorator
Type	Two Type 2.0 Ports
UPC	883778304606

Dimensions

Dimensions	4.12 in x 1.75 in x 1.96 in
Display Size	Standard Sized Product
Height	1.96 in
Length	4.12 in
Width	1.75 in

Electrical Ratings

Amperage Rating	15 A
Connectivity	Back and Side Wired Screw Terminals
Current / Amperage Rating	15 A
Current Rating	15 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	125 V
Voltage Rating Description	125 V
Wattage	1875 W

Conductor Related

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG

Certifications And Compliance

Industry Standard(s)	cULus Listed To UL498
Nema Rating	5-15R

Logistics

Carton Quantity	10

Product Assets

Catalogs - WDK Catalog Full 2024
Specifications - USB15X2W

©2024 Hubbell Incorporated. All rights reserved