KILLARK®

Versamate Series 30A 3 Pole 4 Wire Receptacle Assembly

By Killark
Catalog # VR342

30A 3 Pole 4 Wire Receptacle Assembly



Features

- Patented “Breech-Lock” cap serves as both flip lid and screw cover.
- Patented notch in cap arm holds cap open for easy plug insertion or maintenance.
- Type 4X rating when inserted into VersaMate receptacle and locking ring is tightened.
- Patented pin design uses slotted spring clip which avoids excessive wear while providing continuous electrical pin to sleeve contact.
- “Increased Safety” type box terminals with gripper ribs securely clamp around conductors.
- Boxes come with a green grounding screw.

Application

Suitable for indoor or outdoor use. Applications include the wet, cold, hosedown, hazardous or corrosive areas in such industrial applications as:Pulp & Paper Mills, Electrical Power Plants, Petrochemical Plants, Wastewater Treatment, Marine, Docks, Ports, Construction Sites, Breweries, Refineries, Chemical Plants, Grain Facilities , Textile Manufacturing, Food Processing Facilities

Specifications

Buy America(n) Qualified	Contact Manufacturer
EU RoHS Indicator	Contact Manufacturer

Conductor

Number Of Wires	3

Current

Frequency Rating	50-400 Hz
Amperage Rating	30 A
Voltage Rating	• 600 VAC • 250 VDC

Dimensions

Height	3.89 in
Width	3.41 in
Length	3.25 in
Dimensions	3.25 in x 3.41 in x 3.89 in

General

Style	Style II
UPC	783936834160
Type	Pin & Sleeve
Material	• Body-Copper-free aluminum • Contacts-Brass • Spring tensioner-Patented beryllium copper • External screws-316 stainless steel
Finish Type	Baked Powder Epoxy/Polyester Finish
Series	VersaMate Series

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved