HUBBELL
Wiring Device-Kellems

2" Though Floor Fitting

By Hubbell Wiring Device-Kellems
Catalog # PT27A

Fire-Rated Poke-Through Pedestal Series, 2" Though Floor Fitting



Features

2" Though Floor Fitting

Application

Through Floor Fitting

Performance

- Electrical - Power Wiring Capacity - Up to ten #12 AWG type THHN wires, or Up to six #12 AWG and two #10 AWG type THHN wires
- Electrical - Voice/Data Wiring Capacity - Up to two 25 pair tel./data cables (100 #22 AWG tel./data conductors), or Up to two IBM Type 2 data cables
- Mechanical - Max. Cu Cross Section - 1/2" Power EMT .0461 sq. in., 3/4" Low Voltage EMT .0500 sq. in.
- Mechanical - UL Spacing Restrictions - Min. of 2 ft. O.C. and not more than one unit per each 65 sq. ft. of floor area in each span

General

Catalog Number	PT27A
EU RoHS Indicator	No
Item Type	Through Floor Fitting
Material	Composite
Material - Mounting Hardware	N/A
OEM Brand Name	Hubbell Wiring Device-Kellems
Specifications	• Conduit Tube - 1/2 in. EMT power tube • Floor Thickness - 2 1/4 to 7 in. (57.2 to 177.8) • Mounting - 2 in. (50.8) diameter hole • Service Pedestal Options - FR280, FR480, FR680 Series
Style	Through-Floor Fittings
UPC	783585076157

Dimensions

Display Size	Standard Sized Product

Certifications And Compliance

Industry Standard(s)	• Fire Resistance - R8429 • Outlet Box- E31999

Product Assets

Catalog Page - WDK P-34 Catalog Page
Catalog Page - WDK P-45 Catalog Page
Catalog Page - WDK P-46 Catalog Page
Catalogs - WDK Catalog Full 2024
Engineering Drawing - PT27A AutoCAD Drawing
Installation Manuals - WIRING_PD1901_INSTALLINST
Sales Drawings - WDK_PT27A_DRAWING_PDF
Specifications - PT27A
Warranty - Industrial & Commercial Products

©2025 Hubbell Incorporated. All rights reserved