HUBBELL
Wiring Device-Kellems

2x2 Flush Duplex Series, Complete Unit, Isolated Ground, Brass Finish

By Hubbell Wiring Device-Kellems
Catalog # PT2X2IGBRS



In-Floor Delivery Systems, Fire-Rated Poke-Throughs, 2x2 Flush Duplex Series, Complete Unit, Isolated Ground, Brass Finish

Features

- Complete 3" Fire-Rated Poke-Through
- Prewired 20A IG Duplex Receptacle
- (2) Installed Cat 6 Hubbell Xcelerator Jacks
- Non-metallic Cover with Brushed Brass Flange
- Includes Junction Box

General

Application - For Use On	Carpet
Catalog Number	PT2X2IGBRS
EU RoHS Indicator	No
Finish Type	Brass
Item Type	3" Fire-Rated Poke Through Component
Knockouts	Duplex Flip Covers
Material - Mounting Hardware	Step-Down Installation
Number Of Outlets	(1) Prewired 20A Duplex IG Receptacle; (2) Installed Cat 6 Jacks
Specifications	• Approval - Approved for use in the City of Chicago • Cover and flange - Flush thermoplastic cover with painted aluminum flange • Floor thickness - 2 1/4 to 7 in. (57.2 to 177.8) • Mounting - 3 in. (76.2) cored concrete diameter through hole
Style	FRPT - Complete Kits
UPC	783585531915

Certifications And Compliance

Industry Standard(s)	• cULus Listed • Meets ADA Standards • UL 514A Listed

Logistics

Carton Quantity	1

Product Assets

Catalog Page - WDK P-31 Catalog Page
Catalogs - WDK Catalog Full 2024
Customer Notices - Prop 65 Notice
Engineering Drawing - PT2X2IGBRS AutoCAD Drawing
Installation Manuals - WIRING_PD1936_INSTALLINST
Literature - Delivery Systems Product Guide
Sales Drawings - WDK_PT2X2IGBRS_DRAWINGS_PDF
Specifications - PT2X2IGBRS
Warranty - Industrial & Commercial Products

©2025 Hubbell Incorporated. All rights reserved