HUBBELL
Wiring Device-Kellems

Surge Protective Devices, SPIKESHIELD TVSS Plug Strips, 15A 125V, 7 Oulet, 150 Joules, 6′ Cord, Office White



By Hubbell Wiring Device-Kellems
Catalog # HBL7PS1050A

Surge Protective Devices, SPIKESHIELD TVSS Plug Strips, 15A 125V, 7 Oulet, 150 Joules, 6′ Cord, Office White

Features

- 1050 joule, 6 foot cord, $5,000 down-line warranty
- Tamper tamper resistant shutters.

Application

7 Outlet, Standard Devices

Performance

Electrical - Max Surge Current - 19.5kA, Electrical - Max. Operating Voltage - 130, Electrical - Operating Frequency - 50/60Hz, Environmental - Operating Temperature - -40°F to 160°F (-40°C to 70°C)

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes

Conductor

Cord Length	6 ft

Configuration

Number Of Outlets	7

Current

Current Rating	15 A
Frequency Rating	60 Hz
Phase	Single Phase
Current / Amperage Rating	15 A
Connectivity	Plug-In

Dimensions

Display Size	1050 Joules

General

Series	Economy Surge Strips
OEM Brand Name	Hubbell Wiring Device-Kellems
Outlet	Straight Blade 5-15R
Color	Office White
Item Type	Surge Protection Plug Strips
Material - Mounting Hardware	Portable
Type	Non-Metallic
Material	Non-Metallic
Specifications	• Color - Off. White • Height - 1.85″ (47.0) • Housing - ABS • Length - 14.75″ (374.7) • Width - 2.36″ (59.9)
UPC	783585120553

Logistics

Carton Quantity	10
Pallet Quantity	420

Operational

Response Time	5
Indicator(s) Type	LED Indicator
Operating Temperature	32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)

Product Assets

Catalog [English]
Catalog Page [English]
Catalog Page [English]
Installation Manual [Spanish, French, English]

© 2025 Hubbell Incorporated. All rights reserved