





Recessed 8-Gang Ballroom Series Floor Boxes


Style		CFB8FC Series	
		8-Gang  **CFB8FC1**	8-Gang  **CFB8FC2**
Application		Carpet	Tile, Finished Concrete
Min. Depth of Pour		6.95" (176.5)	7.15" (181.6)
Adjustability		Before Pour	Before Pour
Dimensions:	A B C	6.95" (176.5) 15.00" (381.0) 13.00" (330.2)	7.15" (181.6) 14.75" (374.7) 12.75" (323.9)
KO Trade Size:	Sides Front & Back Bottom	(4) 1", 1¼", 1½" (4) 1", 1¼", 1½" (4) 1", 1¼", 1½"	(4) 1", 1¼", 1½" (4) 1", 1¼", 1½" (4) 1", 1¼", 1½"
Side View Depth behind mounting plate 		X = 2.27" (57.7) Y = 4.01" (101.9) Z = 3.13" (79.5)	X = 2.27" (57.7) Y = 4.01" (101.9) Z = 3.13" (79.5)
Accepts industry standard size wallplates (sold separately) 4.63" Maximum Cover Height		One, two, three and four gang plates. Customer configuration dependant. 	One, two, three and four gang plates. Customer configuration dependant. 


Note: UL File Number E31999.

Accessories

On-grade Barrier
The on-grade barrier is intended for use on installations at grade level. This accessory is installed prior to the concrete pour and provides a barrier between the soil. The on-grade barrier comes with leveling feet and anchor points.

CFBOGPAN4





Pour Pan Dimensions:
15.75 in. sq.
4 in. depth

Covers

	CFB8FC1 Covers		CFB8FC2 Covers	
All ballroom floor box covers are machined from Aluminum and have no additional finish options				
Carpet Cover, with 2 egress doors (0.20" depth)	**CFB8CVRALU1**	–	–	–
Flush cover, with 2 egress doors	–	–	**CFB8CVRALU2**	–
Blank box cover	–	**CFB8JBC1**	–	**CFB8JBC2**
Cover Load Ratings*: Recommended Loading Maximum Load	 20,000 lb 40,000 lb	 20,000 lb 40,000 lb	 20,000 lb 40,000 lb	 20,000 lb 40,000 lb

*Note: *Load applied through 3" (76mm) mandrel in center of cover. Loads are static and don't apply to rolling loads.*

Dimensions in Inches (mm)