


15 and 20 Ampere, 125 and 250 Volts




SNAP2162A




SNAP2162ITRA



SNAP2162GYL



SNAP2162RLTRA



SNAP5661LATR

Dimensions in Inches (mm)

SNAP*Connect*® Extra Heavy Duty Receptacles



15A 125V
NEMA 5-15R
UL CSA
0.5 HP



20A 125V
NEMA 5-20R
UL CSA
1 HP

Style Line® Decorator	Color	Catalog Number	
Specification grade, Style Line® decorator, flush, nylon face, modular receptacle which requires pigtailed connector below.	Black	**SNAP2152BKA**	**SNAP2162BKA**
	Brown	**SNAP2152A**	**SNAP2162A**
	Gray	**SNAP2152GYA**	**SNAP2162GYA**
	Ivory	**SNAP2152IA**	**SNAP2162IA**
	Light Almond	**SNAP2152LAA**	**SNAP2162LAA**
	Red	**SNAP2152RA**	**SNAP2162RA**
	White	**SNAP2152WA**	**SNAP2162WA**
Specification grade, Style Line® decorator, flush, nylon face, modular receptacle which requires pigtailed connector below. Assembled in USA.	Black	**SNAP2152BKNA**	**SNAP2162BKNA**
	Brown	**SNAP2152NA**	**SNAP2162NA**
	Gray	**SNAP2152GYNA**	**SNAP2162GYNA**
	Ivory	**SNAP2152INA**	**SNAP2162INA**
	Light Almond	**SNAP2152LANA**	**SNAP2162LANA**
	Red	**SNAP2152RNA**	**SNAP2162RNA**
	White	**SNAP2152WNA**	**SNAP2162WNA**
Specification grade, Tamper-Resistant, Style Line® decorator, flush, nylon face, modular receptacle which requires pigtailed connector below. Assembled in USA.	Black	**SNAP2152BKTRA**	**SNAP2162BKTRA**
	Blue	**SNAP2152BLTRA**	**SNAP2162BLTRA**
	Brown	**SNAP2152TRA**	**SNAP2162TRA**
	Gray	**SNAP2152GYTRA**	**SNAP2162GYTRA**
	Ivory	**SNAP2152ITRA**	**SNAP2162ITRA**
	Light Almond	**SNAP2152LATRA**	**SNAP2162LATRA**
	Red	**SNAP2152RTRA**	**SNAP2162RTRA**
	White	**SNAP2152WTRA**	**SNAP2162WTRA**
Specification grade, Tamper-Resistant, Split Circuit, Style Line® decorator, flush, nylon face, modular receptacle which requires pigtailed connector below. Assembled in USA.	Black	**SNAP2152BKSCTRA**	**SNAP2162BKSCTRA**
	Blue	**SNAP2152BLSCTRA**	**SNAP2162BLSCTRA**
	Brown	**SNAP2152SCTRA**	**SNAP2162SCTRA**
	Gray	**SNAP2152GYSCTRA**	**SNAP2162GYSCTRA**
	Ivory	**SNAP2152ISCTRA**	**SNAP2162ISCTRA**
	Light Almond	**SNAP2152LASCTRA**	**SNAP2162LASCTRA**
	Red	**SNAP2152RSCTRA**	**SNAP2162RSCTRA**
	White	**SNAP2152WSCTRA**	**SNAP2162WSCTRA**
Isolated ground[Δ], Spec. grade, TR.	Orange	**SNAP2152IGTRA**	**SNAP2162IGTRA**
Spec. grade, with Power Indicating LED, Style Line® decorator, flush, nylon face, modular receptacle which requires pigtailed connector below. Assembled in USA.	Black	**SNAP2152BKL**	**SNAP2162BKL**
	Blue	**SNAP2152BLL**	**SNAP2162BLL**
	Brown	**SNAP2152L**	**SNAP2162L**
	Gray	**SNAP2152GYL**	**SNAP2162GYL**
	Ivory	**SNAP2152IL**	**SNAP2162IL**
	Light Almond	**SNAP2152LAL**	**SNAP2162LAL**
	Red	**SNAP2152RL**	**SNAP2162RL**
	White	**SNAP2152WL**	**SNAP2162WL**
Isolated ground[Δ], Spec. grade, with LED.	Orange	**SNAP2152IGL**	**SNAP2162IGL**
Specification grade, Tamper-Resistant, with Power Indicating LED, Style Line® decorator, flush, nylon face, modular receptacle which requires pigtailed connector below. Assembled in USA.	Black	**SNAP2152BKLTRA**	**SNAP2162BKLTRA**
	Blue	**SNAP2152BLLTRA**	**SNAP2162BLLTRA**
	Brown	**SNAP2152LTRA**	**SNAP2162LTRA**
	Gray	**SNAP2152GYLTRA**	**SNAP2162GYLTRA**
	Ivory	**SNAP2152ILTRA**	**SNAP2162ILTRA**
	Light Almond	**SNAP2152LALTRA**	**SNAP2162LALTRA**
	Red	**SNAP2152RLTRA**	**SNAP2162RLTRA**
	White	**SNAP2152WLTRA**	**SNAP2162WLTRA**
Isolated ground[Δ], Spec. grade, TR with LED.	Orange	**SNAP2152IGLTRA**	**SNAP2162IGLTRA**

Note: [Δ]See section N additional information on isolated ground devices.
See page Tech-10 for Tamper-Resistant and LED Power Indicators descriptions.
See pages A-47 and A-48 for accessories.
See section O for wallplates.

SNAP*Connect*® 250V Extra Heavy Duty Standard Single Receptacles

Description	Color	15A 250V	20A 250V
Spec. grade, single modular receptacle Tamper-Resistant, smooth nylon face. Requires pigtailed connector on page A-13.	Black	**SNAP5661BKTR**	**SNAP5461BKTR**
	Brown	**SNAP5661BTR**	**SNAP5461BTR**
	Gray	**SNAP5661GYTR**	**SNAP5461GYTR**
	Ivory	**SNAP5661ITR**	**SNAP5461ITR**
	Light Almond	**SNAP5661LATR**	**SNAP5461LATR**
	White	**SNAP5661WTR**	**SNAP5461WTR**