HUBBELL
Premise Wiring

# Non-Metallic Raceway, Latching LANTRAK, Base and Cover, 5′ Length



By Hubbell Premise Wiring
Catalog # PL1BC5

Non-Metallic Raceway, Latching LANTRAK, Base and Cover, 5′ Length

## Features

- UL Listed and CSA Certified to 600 volts
- Single and two channel latching raceways are dual-rated for both power and data applications, reducing inventory requirements

## Application

5′ Base and Cover

## Performance

Environmental - Flame Rating - UL94V-0, Environmental - Temperature Range - -25.6° to 158° F

## Specifications

| | |
|---|---|
| Non Hazardous Location | Non Hazardous |
| Industry Standard(s) | • CSA Standard C22.2 no. 62<br>• E118895 / E119190<br>• UL Standard UL 5A |
| EU RoHS Indicator | Yes |

## Configuration

| | |
|---|---|
| Knockouts | None |

## Dimensions

| | |
|---|---|
| Width | 1.38 in |
| Length | 5 ft |

## General

| | |
|---|---|
| Item Type | PL1, LanTrak- Latching |
| Construction | Extruded Plastic |
| Type | Base and Cover |
| Enclosure Type | NEMA 1 Rating |
| Series | PL1 |
| Cover Type | Integral |
| Material | Thermoplastic |
| Specifications | • Crush Resistance - 300 lbs.<br>• Impact Resistance - 5 ft. lbs.<br>• Length - 5 ft. (1.5m)<br>• Material - UV Stabilized PVC |
| UPC | 783585090238 |
| Style | Single Channel, Latching |
| Color | Office White |

## Logistics

| | |
|---|---|
| Carton Quantity | 50 |

## Product Assets

Catalog [English]
Catalog [English]
Catalog Page [English]



© 2026 Hubbell Incorporated. All rights reserved