HUBBELL
Premise Wiring

Fiber Optic Panel Adapter, 12-Fiber, 6 LC Duplex, Zircon Sleeves, Blue

By Hubbell Premise Wiring
Catalog # FSPNLCDS6B

Fiber Optic Panel Adapter, 12-Fiber, 6) LC Duplex, Zircon Sleeves, Blue



Features

- Premium Quality and High Performance Design

Application

Interconnect

Performance

Optical - SM/MM insertion loss - Less than 0.50dB (0.25dB typical), Environmental - Operating temperature - 0 ºC to +75 ºC

Specifications

Industry Standard(s)	• TIA-568-C.3 • TIA-604-FOCIS

Conductor

Fiber Size	125 Micron
Fiber Type	Singlemode or Multimode

Configuration

Number Of Ports	6

Current

Return Loss	56
Insertion Loss	0.30 dB

General

Sub Brand	OptiChannel
Color	Blue
Material - Mounting Hardware	Snap-In
Material	Ceramic Zirconium
UPC	662620671895

Logistics

Carton Quantity	4
Pallet Quantity	1800

Operational

Adapter Type	LC Duplex
Temperature Rating	-40C to +85C
Repeatability	0.1 dB SM / 0.2 dB MM
Service Life	500 matings
Single/Multimode	SM/MM

Product Assets

Catalog [English]
Catalog Page [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved