Product data sheet
Characteristics

9007FTUC4
LIMIT SWITCH 600VAC 30AMP FT+OPTIONS

Main

Device application	Standard foundry switch Universal mill switch
Device short name	FT
Series name	Severe duty

Complementary

[Ith] conventional free air thermal current	20 A
[Ui] rated insulation voltage	600 V
Base plate style	Style C
Body material	Cast zinc
Contact code designation	A600 P600
Contacts material	Silver flashed copper
Contact operation	Snap action
Maximum displacement angle	81 °
Positive opening	Without
Switch actuation	CW and CCW
Tilting angle	6 °
Torque value	12 lbf.in (1.36 N.m)
Tripping angle	5 °

Environment

Ambient air temperature for operation	-10…185 °F (-23…85 °C)
Electrical shock protection class	Class 0
IP degree of protection	IP65 IP67 IP66
NEMA degree of protection	NEMA 1/2/4/12/13
Product certifications	CE UL listed CSA
Protective treatment	Corrosion resistant gray paint
Shock resistance	30 gn
Standards	UL 508

Ordering and shipping details

Category	21497 - 9007 FT,T OILTIGHT AND FOUNDRY
Discount Schedule	DS1
GTIN	00785901638186
Returnability	No
Country of origin	MX

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months