Product data sheet
Characteristics

8903SPC81V02
Contactor, Night Master, combination lighting, 60A, 3 pole, breaker, 110/120VAC 50/60Hz coil. NEMA 3R



Main

Product	Combination electrically held lighting contactor
Type	Night-Master

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	60 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Disconnector device type	Thermal magnetic circuit breaker, 60 A 600 V
Electrical Connection	Lugs
Height	23.50 in (597 mm)
Depth	10.51 in (267 mm)
Width	15.00 in (381 mm)

Environment

Enclosure Type	NEMA 3R painted sheet steel surface none
Product Certifications	UL listed file E16151 CCN NRNT

Ordering and shipping details

Category	21326-8903 S*C
Discount Schedule	CP1
GTIN	785901779919
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23.50 in (59.7 cm)
Package 1 Width	15.00 in (38.1 cm)
Package 1 Length	10.51 in (26.7 cm)
Package 1 Weight	105.00 lb(US) (47.627 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months