
# Product data sheet
## Characteristics

# 8911DPSO52V02
NEMA starter, Type DPS, reversing, horizontal, Size 4, 135A, 100 HP at 575VAC, 10 kA SCCR, 3 phase, 3 pole, melting alloy overload, 120VAC coil, open



## Main

| | |
|---|---|
| Product | Definite Purpose Starter |
| Ampere Rating | 50 A |
| Horsepower Rating | 3 Hp 115 V AC, 1 phase<br>10 hp 230 V AC, 1 phase |
| Maximum Voltage Rating | 600 V AC |
| Control Circuit Voltage | 110 V AC 50 Hz<br>120 V AC 60 Hz |
| Phase | 1 phase |

## Complementary

| | |
|---|---|
| Enclosure Rating | Not rated (open device) |
| Locked Rotor Amperes | 300 A 230 V AC<br>250 A 460 V AC<br>200 A 575 V AC |
| Number of Poles | 2P |
| Range | DPS |
| Overload Type | Melting alloy |
| Number of Thermal Units | 1 |

## Ordering and shipping details

| | |
|---|---|
| Category | 21381-8911 DP |
| Discount Schedule | CP1 |
| GTIN | 785901779322 |
| Returnability | No |
| Country of origin | CN |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.00 in (12.7 cm) |
| Package 1 Width | 5.00 in (12.7 cm) |
| Package 1 Length | 8.00 in (20.32 cm) |
| Package 1 Weight | 3.00 lb(US) (1.361 kg) |

## Offer Sustainability

| | |
|---|---|
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Contractual warranty

| | |
|---|---|
| Warranty | 18 months |